



R31 =	33	KΩ	0,125W	± 5%
R32 =	82	KΩ	0,125W	± 5%
R33 =	1,2	KΩ	0,125W	± 5%
R34 =	1	KΩ	0,125W	± 5%
R35 =	560	KΩ	0,125W	± 5%
R36 =	82	KΩ	0,125W	± 5%
R37 =	470	Ω	0,125W	± 5%
R38 =	1	KΩ	0,125W	± 5%
R39 =	15	KΩ	0,125W	± 5%
R40 =	2,2	KΩ	0,125W	± 5%
R41 =	1	KΩ	0,125W	± 5%
R42 =	560	Ω	0,125W	± 5%
R43 =	470	Ω	0,125W	± 5%
R44 =	4,7	KΩ	0,125W	± 5%
R45 =	470	Ω	0,125W	± 5%
R46 =	5,6	KΩ	0,125W	± 5%

C31 =	TRIMMER	
C32 =	139	pF VARIABILE
C33 =	40	nF 150 Vcc
C34 =	40	nF 150 Vcc
C35 =	20	nF 150 Vcc
C36 =	1,5	nF 25 Vcc ± 5%
C37 =	TRIMMER	
C38 =	90	pF VARIABILE
C39 =	10	μF 12 Vcc
C40 =	20	nF 150 Vcc
C41 =	10	nF 150 Vcc
C42 =	1,5	nF 33 Vcc ± 5%
C43 =	20	nF 150 Vcc
C44 =	100	μF 12 Vcc
C45 =	10	nF 150 Vcc
C46 =	1,5	nF 33 Vcc ± 5%
C47 =	4,7	nF 125 Vn
C48 =	4,7	nF 125 Vn
C49 =	20	nF 50 Vcc
C50 =	4,7	nF 125 Vn

Tr 1 =	AF 116
Tr 2 =	AF 117
Tr 3 =	AF 117
Rd =	0A 90
Z1 =	Dm 18757

SIMBOLI CONDENSATORI



- Schema del Radiosintonizzatore.